# IBM

## Highlights

- Help reduce costs with lower power consumption, consolidation and space reduction
- Support media partitioning on Linear Tape-Open (LTO) Ultrium 5 media
- Simplify data management with IBM® Spectrum Archive™ utilizing IBM Linear Tape File System™ (LTFS) technology
- Address backup and archiving requirements with lower cost implementation

# IBM TS2250 tape drive

Fifth-generation LTO Ultrium half-height tape drive

Today, data is a key corporate asset in all types of businesses. The ability to access data quickly and reliably is critical to your success. The main challenge for midmarket chief information officers (CIOs) is how to cost-effectively store, archive and retrieve an explosion of new information; how to protect and secure that information; and how to meet compliance requirements and make information accessible for business insight, where and when it's needed.

The IBM TS2250 tape drive—the entry-level IBM tape product family offering—is the answer to growing storage requirements. Incorporating the industry-leading LTO Ultrium technology, the TS2250 tape drive is suited for handling backup, save and restore, and archival data storage needs with higher capacity and higher data transfer rate than previous generations. In addition, IBM LTO Ultrium 5 technology is designed to support media partitioning, and LTFS technology. It also continues to support encryption of data and write-once-read-many (WORM) media.

The TS2250 tape drive is an excellent tape storage solution for businesses requiring backup and low-cost, archival storage of their data. TS2250 provides a physical storage capacity of up to 3.0 TB (with 2:1 compression) in conjunction with the IBM LTO Ultrium 1.5 TB data cartridge,



nearly double the capacity of LTO Ultrium 4 cartridges. The data transfer performance of the TS2250 tape drive has increased over the previous LTO Ultrium half-height generation with a transfer rate of up to 140 MBps with 6 Gbps SAS interface connectivity. The drive offers two SAS and one Ethernet port per drive to improve availability.



#### **Advanced features**

The TS2250 tape drive features 6 Gbps SAS interface for connection to a wide spectrum of open-system servers. TS2250 is designed to address your backup and restore needs. The LTO Ultrium 5 tape media provides partitioning support, which,

in conjunction with LTFS technology available via IBM Spectrum Archive, provides customers with the ability to have file-level access to tape data. This support helps quickly locate and update information on the tape media.

LTO Ultrium 5 technology is also designed to support encryption of data. The hardware encryption and decryption core and control core reside in the LTO Ultrium 5 tape drive. In addition to reading and writing to LTO Ultrium 5 tape cartridges, TS2250 can read and write to LTO Ultrium 4 cartridges and read LTO Ultrium 3 cartridges.

### Software support

You can help increase the power of the TS2250 tape drive by managing it with tape management solutions such as IBM Spectrum<sup>™</sup> Protect or other, third-party, storage software.

#### Media

You can order data and cleaning cartridges for the TS2250 tape drive at the time of purchase or from IBM Media, IBM Supplies distribution and authorized dealers. Call 1-888-IBM-Media (1-888-426-6334) toll free in the United States and Canada.

| IBM TS2250 tape drive at a glance |   |
|-----------------------------------|---|
| Available configurations          | Model 3580 H5S—One LTO Ultrium 5 tape drive, 6 Gbps SAS interface PN 3580S5E  |
| Tape drive type                   | IBM LTO Ultrium 5   |
| Physical capacity                 | 1.5 TB Native; 3.0 TB with 2:1 compression  |
| Number of tape drives             | 1   |
| Number of tape cartridges         | 1   |
| Data transfer rate                | Up to 140 MBps native   |
| Media type                        | IBM LTO 5 data cartridge IBM LTO cleaning cartridge Call 1-888-IBM-Media  |
| Weight                            | 4.3 kg (9.5 lb)   |
| Power requirements                | 100 - 240 V ac, 50 - 60 Hz autoranging  |
| <b>Dimensions</b> (W x H x D)     | 21.3 cm × 5.8 cm × 33.2 cm (8.39 in. × 2.29 in. × 13.07 in.)  |
| Warranty                          | Three-year limited warranty, customer-replaceable unit (CRU) and on-site service in most countries, next business day 9x5, service upgrades available |

#### For more information

To learn more about the IBM TS2250 tape drive, please contact your IBM representative or IBM Business Partner, or visit:

- ibm.com/systems/storage/tape/ts2250/index.html
- ibm.com/systems/storage/product/tape.html
- ibm.com/systems/storage/news/center/tape/lto/index.html

Additionally, IBM Global Financing can help you acquire the IT solutions that your business needs in the most cost-effective and strategic way possible. For credit-qualified clients we can customize an IT financing solution to suit your business requirements, enable effective cash management, and improve your total cost of ownership. IBM Global Financing is your smartest choice to fund critical IT investments and propel your business forward. For more information, visit: <a href="https://ibm.com/financing">ibm.com/financing</a>



© Copyright IBM Corporation 2015

IBM Systems Route 100 Somers, NY 10589

Produced in the United States of America August 2015

IBM, the IBM logo, ibm.com, IBM Spectrum Archive, IBM Spectrum, and Linear Tape File System are trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the web at "Copyright and trademark information" at <a href="https://ibm.com/legal/copytrade.shtml">https://ibm.com/legal/copytrade.shtml</a>

Linear Tape-Open, LTO, the LTO Logo, Ultrium and the Ultrium logo are trademarks of HP, IBM Corp. and Quantum in the U.S. and other countries

This document is current as of the initial date of publication and may be changed by IBM at any time. Not all offerings are available in every country in which IBM operates.

The performance data discussed herein is presented as derived under specific operating conditions. Actual results may vary. It is the user's responsibility to evaluate and verify the operation of any other products or programs with IBM products and programs.

THE INFORMATION IN THIS DOCUMENT IS PROVIDED "AS IS" WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT. IBM products are warranted according to the terms and conditions of the agreements under which they are provided.

Actual available storage capacity may be reported for both uncompressed and compressed data and will vary and may be less than stated.



Please Recycle